

## BAROZZI PAINT

**WASHABLE, ACRYLIC, WATER-BASED PAINT FOR INTERIORS.  
HIGHLY COVERING AND WITH EXCELLENT RESISTANCE.**

<b>TYPE OF BINDER</b>	Acrylic in aqueous emulsion
<b>ASPECT OF DRY FILM</b>	Velvet-like matt
<b>WET-SCRUB RESISTANCE</b>	CLASS 1 [UNI EN ISO 11998:2006]
<b>AVAILABLE COLOURS</b>	White and UNISYSTEM tinting system
<b>SPECIFIC WEIGHT</b>	1,54 kg/lit +/- 0,02 at 20° C
<b>VISCOSITY</b>	15.000 cps +/- 2.000 (A6 V20 BROOKFIELD at 20° C)
<b>APPLICATION (5°C ≤ T ≤ 30°C)</b>	Brush – Roller – Spray
<b>DILUTION</b>	30 - 40 % with clear water
<b>APPROXIMATE YIELD</b>	8 - 9 sqm/Lt per coat
<b>DRYING at 20°C</b>	Touch dry: 15-20 minutes / Thoroughly dry: 24 hours
<b>OVERCOATING INTERVAL</b>	4 - 5 hours
<b>V.O.C CONTENT</b>	Less than 20 gr/lit [Directive 2004/42/CE: (cat. A/a WB: 30)]
<b>STORAGE AND SHELF LIFE</b>	Store in a cool, dry, well ventilated area away from heat and direct sunlight. The product has a shelf life of 12 months when kept in original sealed packaging. It must be protected from frost.

### CHARACTERISTICS AND FIELD OF APPLICATION

BAROZZI PAINT is suitable as opaque finishing for interiors where excellent washability and covering properties are required. BAROZZI PAINT is also suitable as matt and velvet-like finishing for concrete and masonry surfaces of civil and industrial buildings where good protection and excellent covering properties are required.

It can be dyed with universal pigments. The diluted product must be used within 2-3 days.

The wet-scrub resistance is determined in accordance with the test method UNI EN ISO 11998:2006 "Determination of wet-scrub resistance and cleanability of coatings" through the measure of the loss of dry filmthickness (ref. UNI EN 13300:2002) [The report 472/L date 11.10.2019 performed by GFC Chimica s.r.l. is available upon request].

### SUBSTRATE PREPARATION

**NEW WALLS:** the surface must be properly prepared, dry, clean, brushed, dusted off and free from any kind impurity. In case of need, apply one coat of insulating fixative **MURACRIL**, in order to consolidate the substrate.

**WALLS WITH EXISTING PAINTWORK:** brush and clean the surface in order to remove flaking paints and anything that is not perfectly anchored to the surface. In case of need, plaster and apply one coat of fixative. In case of moulds ensure suitable treatment with **LINDOFIX** (for interiors) or **LINDOSTOP** (for exteriors). Then, proceed as for new surface.

### WARNINGS

Apply the product in the climatic conditions as mentioned above. Inappropriate conditions of application of the product are adversely affected in the drying time and the achievement of the optimum appearance and performance can be compromised. Drying may take longer when temperatures are lower and humidity is higher and some unsightly looking, translucent and sticky drops could appear. This temporary phenomenon does not affect the performance of the product and may be removed by washing the surface or waiting for the next rainfall event.

The product complies with C.L.P. European Regulation, in force from 1<sup>st</sup> June 2015.

*All our products are of a high quality and subject to rigid quality control. The information given in this specification sheet is for guidance and is given in good faith but no liability can be assumed by Barozzi Vernici S.r.l. for the performance of the products and for final results, since skills of application and site conditions are beyond our direct control. The information contained in this document is strictly confidential and shall be the sole and exclusive property of Barozzi Vernici S.r.l..*