BEN HUR

SELF-ADHESIVE STUCCO POWDER FOR WOOD, WALLS AND GYPSUM.

AVAILABLE COLOURS	White
COMPOSITION	Inert mineral fillers, carbonates, gypsum plaster and cellulose
APPLICATION (5°C ≤ T ≤ 35°C)	Putty knife
DRYING at 20°C	24 hours
STORAGE	Store in a dry area
SHELF LIFE	The product has a shelf life of 12 months when kept in original sealed packaging. It must be protected from frost.

CHARACTERISTICS AND FIELD OF APPLICATION

It is characterized by the remarkable filling power, the adhesive power and the workability also with dry sanding.
It can be painted over both with water-based and solvent based products.
Apply BEN HUR with a putty knife: mix 2 parts of putty powder with 1 part of water, until a homogeneous paste is obtained. The pot-life of the mixture is about 120 minutes. In case of need/according to the work it can be thinned more, obtaining longer drying times. It is suitable for smoothing wall surfaces, for the application of decorative stuccos, rosettes and frames.
It can be used to fill even craks and holes on walls, wood, building slabs etc.
In presence of consistent humidity, add boiled linseed oil to the mixture of BEN HUR.

SUBSTRATE PREPARATION

Dilute only the quantity of product needed, since once it has hardened, the product can no longer be usable. Wash brushes and tools with water after use. Wash tools with water immediately after use.

WARNINGS

Apply the product in the climatic conditions as mentioned above. Inappropriate conditions of application of the product are adversely affected in the drying time and the achievement of the optimum appearance and performance can be compromised. Drying may take longer when temperatures are lower and humidity is higher and some unsightly looking, translucent and sticky drops could appear. This temporary phenomenon does not affect the performance of the product and may be removed by washing the surface or waiting for the next rainfall event.

The product complies with C.L.P. European Regulation, in force from 1st June 2015.

All our products are of a high quality and subject to rigid quality control. The information given in this specification sheet is for guidance and is given in good faith but no liability can be assumed by Barozzi Vernici S.r.l. for the performance of the products and for final results, since skills of application and site conditions are beyond our direct control. The information contained in this document is strictly confidential and shall be the sole and exclusive property of Barozzi Vernici S.r.l..