



ELASTOFOND 03

FILLING BASE FOR ELASTOMERIC SYSTEMS.

TYPE OF BINDER	Acrylic styrene
ASPECT OF DRY FILM	Rough, with granulometry 0,3 mm
AVAILABLE COLOURS	White and UNISYSTEM tinting system (pastel shades)
SPECIFIC WEIGHT	1,420 Kg/lt +/- 0,05 at 20° C
VISCOSITY	15.000 cps +/- 2000 at 20° C
APPLICATION (5°C ≤ T ≤ 30°C)	Brush - Roller
DILUTION	5 – 15% with clear water
APPROXIMATE YIELD	5 – 6 sqm/lt. per coat
DRYING at 20°C	8 – 10 hours
OVERCOATING INTERVAL	16 hours with elastomeric products
V.O.C CONTENT	Less than 40 gr/lt [Directive 2004/42/CE: (cat. A/c WB: 40)]
STORAGE AND SHELF LIFE	Store in a cool, dry, well ventilated area away from heat and direct sunlight. The product has a shelf life of 12 months when kept in original sealed packaging. It must be protected from frost.

CHARACTERISTICS AND FIELD OF APPLICATION

It is an elastomeric, pigmented, filling base with special high flexible copolymers in aqueous dispersion. It is suitable as intermediate ground to be applied on elastomeric wall painting cycles in presence of hairline cracks.

The thinned product must be used within 2-3 days.

SUBSTRATE PREPARATION

NEW WALLS: ensure that the surface has matured for at least 28 days and that is dry, clean and free from any type of impurity, included non-adhering sand. Apply one coat of water-based isolating fixative as **NANOFIX** or **MURACRIL**, in order to increase adherence, eliminate surface pulverization and reduce paint consumption.

WALL WITH EXISTING PAINTWORK: remove all existing detaching paintworks by scraping and brushing. Then proceed with the application of isolating fixative as mentioned above. In case of dirt and moulds ensure suitable treatment: wash with high-pressure washer and apply **LINDOSTOP**.

WARNINGS

Apply the product in the climatic conditions as mentioned above. Inappropriate conditions of application of the product are adversely affected in the drying time and the achievement of the optimum appearance and performance can be compromised. Drying may take longer when temperatures are lower and humidity is higher and some unsightly looking, translucent and sticky drops could appear. This temporary phenomenon does not affect the performance of the product and may be removed by washing the surface or waiting for the next rainfall event.

The product complies with C.L.P. European Regulation, in force from 1st June 2015.

All our products are of a high quality and subject to rigid quality control. The information given in this specification sheet is for guidance and is given in good faith but no liability can be assumed by Barozzi Vernici S.r.l. for the performance of the products and for final results, since skills of application and site conditions are beyond our direct control. The information contained in this document is strictly confidential and shall be the sole and exclusive property of Barozzi Vernici S.r.l..