

FILL & FINISH

ACRYLIC-SILOXANE, ANTI-ALGAE, FILLING AND UNIFORMING PRIMER-FINISHING PAINT.

TYPE OF BINDER	Modified Acrylic Resin
ASPECT OF DRY FILM	Matt, rough (granulometry up to 0,7 mm)
AVAILABLE COLOURS	White and UNISYSTEM tinting system
SPECIFIC WEIGHT	1,53 kg/lt +/- 0,02 at 20° C
VISCOSITY	22.000 cps +/- 1000 (A6 V20 BROOKFIELD at 25° C)
APPLICATION (5°C ≤ T ≤ 30°C)	Brush – Roller
DILUTION	15 – 20% with clear water
APPROXIMATE YIELD	4 – 5 sqm/lt per coat
DRYING at 20°C	Out of dust: 30 minutes / Thoroughly dry: 6 – 8 hours
OVERCOATING INTERVAL	5 – 7 hours
V.O.C CONTENT	Less than 40 gr/lt [Directive 2004/42/CE: (cat. A/c BA: 40)]
STORAGE AND SHELF LIFE	Store in a cool, dry, well ventilated area away from heat and direct sunlight. The product has a shelf life of 12 months when kept in original sealed packaging. It must be protected from frost.

CHARACTERISTICS AND FIELD OF APPLICATION

It is suitable as primer-finishing paint for adequately prepared surfaces, where there are small defects and therefore highly covering and highly filling power is required. It is also ideal as a fine, antique-looking, rough finishing. In order to avoid material accumulation, a uniform application is recommended.

The thinned product must be used within 2-3 days. It can be colored with universal pigments as UNYSYSTEM.

SUBSTRATE PREPARATION

NEW WALLS: the surface must be dry, brushed and sealed with one coat of insulating fixative as **PRIMER-SIL** or **NANOFIX**. After 5 – 7 hours apply **FILL&FINISH**.

WALLS WITH EXISTING PAINTWORK: ensure the substrate is dry and clean. If necessary, brush the surface or clean it up thoroughly with high pressure washing machine, in order to remove anything that is not perfectly anchored to the substrate.

In case of dirt and moulds ensure suitable treatment with **LINDOSTOP**. Then, proceed as for new surface.

WARNINGS

Apply the product in the climatic conditions as mentioned above. Inappropriate conditions of application of the product are adversely affected in the drying time and the achievement of the optimum appearance and performance can be compromised. Drying may take longer when temperatures are lower and humidity is higher and some unsightly looking, translucent and sticky drops could appear. This temporary phenomenon does not affect the performance of the product and may be removed by washing the surface or waiting for the next rainfall event.

The product complies with C.L.P. European Regulation, in force from 1st June 2015.

All our products are of a high quality and subject to rigid quality control. The information given in this specification sheet is for guidance and is given in good faith but no liability can be assumed by Barozzi Vernici S.r.l. for the performance of the products and for final results, since skills of application and site conditions are beyond our direct control. The information contained in this document is strictly confidential and shall be the sole and exclusive property of Barozzi Vernici S.r.l.