

GOLD

BREATHABLE, WATER-BASED PAINT FOR INTERIORS, OPAQUE, WITH HIGH COVERING PROPERTIES AND EASY TO APPLY.

TYPE OF BINDER	Styrene-acrylic Apeo free in aqueous emulsion
ASPECT OF DRY FILM	Velvet-like matt, smooth
AVAILABLE COLOURS	White and UNISYSTEM tinting system (pastel shades)
SPECIFIC WEIGHT	1,64 kg/lt +/- 0,03 at 20° C
VISCOSITY	14.000 cps +/- 2.000 (A6 V20 BROOKFIELD at 20° C)
APPLICATION (5°C ≤ T ≤ 30°C)	Brush – Roller – Spray
DILUTION	Up to 30% with clear water
APPROXIMATE YIELD	8 -8,5 sqm/lt per coat
DRYING at 20°C	Out of dust: 10 minutes / Touch dry: 40-60 minutes / Thoroughly dry: 3-4 hours
OVERCOATING INTERVAL	4 hours
V.O.C CONTENT	Less than 30 gr/lt [Directive 2004/42/CE: (cat. A/a WB: 30)]
STORAGE AND SHELF LIFE	Store in a cool, dry, well ventilated area away from heat and direct sunlight. The product has a shelf life of 12 months when kept in original sealed packaging. It must be protected from frost.

CHARACTERISTICS AND FIELD OF APPLICATION

It is suitable as water-based, breathable, high-opacity and highly covering paint for interiors. It is very easy to use both by brush and roller; controlled rheology. It maintains the right viscosity on walls, during application. Thanks to the new formulation, the product dries quickly and allows faster painting system, reducing the waiting times between one coat and the next ones. No unpleasant odor thanks to the recipe without plasticizers and free formaldehyde.

SUBSTRATE PREPARATION

NEW WALLS (plaster, gypsum, plasterboard): the substrate must be properly prepared, dry, clean, cured, dusted off and free from any kind impurity or anything is not perfectly anchored to the surface (sand included). Apply one coat of fixative **MURACRIL**, properly thinned, to consolidate the substrate, avoid chalking and reduce paint consumptions.

WALLS WITH EXISTING PAINTWORK (lime, tempera paint or breathable paint): brush and scrape the surface in order to remove flaking paints. Then apply the fixative as mentioned above. In case of moulds ensure suitable treatment with **LINDOFIX**.

WARNINGS

Apply the product in the climatic conditions as mentioned above. Inappropriate conditions of application of the product are adversely affected in the drying time and the achievement of the optimum appearance and performance can be compromised. Drying may take longer when temperatures are lower and humidity is higher and some unsightly looking, translucent and sticky drops could appear. This temporary phenomenon does not affect the performance of the product and may be removed by washing the surface or waiting for the next rainfall event.

The product complies with C.L.P. European Regulation, in force from 1st June 2015.

All our products are of a high quality and subject to rigid quality control. The information given in this specification sheet is for guidance and is given in good faith but no liability can be assumed by Barozzi Vernici S.r.l. for the performance of the products and for final results, since skills of application and site conditions are beyond our direct control. The information contained in this document is strictly confidential and shall be the sole and exclusive property of Barozzi Vernici S.r.l..