

## IDEAL LACK

**SATIN-FINISH, WATER-BASED, ACRYLIC ENAMEL FOR INTERIORS, SUITABLE FOR FOOD CONTACT SURFACES; IT IS HACCP CERTIFIED AND 1 CLASS WASHABILITY ACCORDING TO UNI EN ISO 11998 STANDARDS.**

<b>TYPE OF BINDER</b>	Modified acrylic in water dispersion.
<b>ASPECT OF DRY FILM</b>	Satin
<b>AVAILABLE COLOURS</b>	White and UNISYSTEM tinting system (pastel shades)
<b>SPECIFIC WEIGHT</b>	1,28 kg/lit +/- 0,05 at 20° C
<b>VISCOSITY</b>	4000 cps +/- 1000 cps
<b>APPLICATION (5°C ≤ T ≤ 30°C)</b>	Brush – roller
<b>DILUTION</b>	Ready to use; max. 3 – 5 % with clear water
<b>APPROXIMATE YIELD</b>	12 - 13 sqm/lit per coat
<b>DRYING at 20°C</b>	Out of dust: 25 – 30 minutes / Touch dry: 45 – 60 minutes / Thoroughly dry: 18 – 24 hours
<b>OVERCOATING INTERVAL</b>	24 hours
<b>V.O.C CONTENT</b>	Less than 140 gr/lit [Directive 2004/42/CE: (cat. A/i WB: 140)]
<b>STORAGE AND SHELF LIFE</b>	Store in a cool, dry, well ventilated area away from heat and direct sunlight. The product has a shelf life of 12 months when kept in original sealed packaging. It must be protected from frost.

## CHARACTERISTICS AND FIELD OF APPLICATION

It is ideal for food contact environments such as lunch rooms, restaurants, kitchens, gastronomy, wineries, cold rooms, food storage warehouses, etc. Thanks to its formulation, it can be used in hospitals, schools, clinics, dental offices, etc. It guarantees high standards of cleanability, washability and resistance to dirt and mould. It is excellent for applications on internal walls and ceilings where washability with alkaline or disinfectant is required.

## SUBSTRATE PREPARATION

**MASONRY OR GYPSUM:** the surface must be dry, brushed and sealed with one coat of insulating fixative **NANOFIX**, properly thinned, to consolidate the substrate.

**WALLS WITH EXISTING PAINTWORK:** brush and clean the surface in order to remove flaking paints and anything that is not perfectly anchored to the substrate. In case of moulds ensure suitable treatment with **LINDOFIX**. Then, proceed as for new surface.

## WARNINGS

Apply the product in the climatic conditions as mentioned above. Inappropriate conditions of application of the product are adversely affected in the drying time and the achievement of the optimum appearance and performance can be compromised. Drying may take longer when temperatures are lower and humidity is higher and some unsightly looking, translucent and sticky drops could appear. This temporary phenomenon does not affect the performance of the product and may be removed by washing the surface or waiting for the next rainfall event.

The product complies with C.L.P. European Regulation, in force from 1<sup>st</sup> June 2015.

*All our products are of a high quality and subject to rigid quality control. The information given in this specification sheet is for guidance and is given in good faith but no liability can be assumed by Barozzi Vernici S.r.l. for the performance of the products and for final results, since skills of application and site conditions are beyond our direct control. The information contained in this document is strictly confidential and shall be the sole and exclusive property of Barozzi Vernici S.r.l.*