IDROREP

SILOXANE, WATER-REPELLENT, WATER-BASED SOLUTION (IDEAL FOR PLASTERS "INTONACHINO").

TYPE OF BINDER	Modified water-based siloxane
ASPECT OF DRY FILM	Matt
AVAILABLE COLOURS	Transparent
SPECIFIC WEIGHT	1,03 kg/lt +/- 0,05 at 20°C
VISCOSITY	10" ford viscosity cup F4 +/- 2" at 20°C
APPLICATION (5°C ≤ T ≤ 30°C)	Brush – Roller
DILUTION	Ready to use
APPROXIMATE YIELD	5 – 6 sqm/lt per coat
DRYING at 20°C	Out of dust: 2 – 3 hours / Thoroughly dry: 6 – 8 hours
OVERCOATING INTERVAL	Normally it is quite one handed
STORAGE AND SHELF LIFE	Store in a cool, dry, well ventilated area away from heat and direct sunlight. The product has a shelf life of 12 months when kept in original sealed packaging. It must be protected from frost.

CHARACTERISTICS AND FIELD OF APPLICATION

It is suitable as water-repellent, non-fill forming solution for all vertical wall surfaces to create a waterproof effect. The aesthetic appearance and the breathability of the substrate remain unaltered. The waterproof property is effective after 2-3 days from the application. Compared to traditional waterproofing solutions, it remains water-repellent for many years. It is the ideal treatment for lime based plasters.

SUBSTRATE PREPARATION

The substrate (concrete, masonry, bricks, travertine, limestone) must be dry, clean and brushed. Apply one coat of diluted fixative **NANOFIX** to consolidate the surface.
Apply until the substrate is completely saturated.
In case of mould ensure suitable treatment with **LINDOSTOP**.

WARNINGS

Apply the product in the climatic conditions as mentioned above. Inappropriate conditions of application of the product are adversely affected in the drying time and the achievement of the optimum appearance and performance can be compromised. Drying may take longer when temperatures are lower and humidity is higher and some unsightly looking, translucent and sticky drops could appear. This temporary phenomenon does not affect the performance of the product and may be removed by washing the surface or waiting for the next rainfall event.

The product complies with C.L.P. European Regulation, in force from 1st June 2015.

All our products are of a high quality and subject to rigid quality control. The information given in this specification sheet is for guidance and is given in good faith but no liability can be assumed by Barozzi Vernici S.r.l. for the performance of the products and for final results, since skills of application and site conditions are beyond our direct control. The information contained in this document is strictly confidential and shall be the sole and exclusive property of Barozzi Vernici S.r.l..