

**WATER-BASED PAINTS FOR INTERIORS****Technical Data Sheet Code 207 Ref. 1909****MAXICOLOR****WATER-BASED, BREATHABLE, HIGHLY COVERING PAINT FOR INTERIORS.**

TYPE OF BINDER	Vinyl-versatic in aqueous emulsion
ASPECT OF DRY FILM	Matt
AVAILABLE COLOURS	White
SPECIFIC WEIGHT	1,71 kg/l $\pm$ 0,02 at 20° C
VISCOSITY	15.000 cps $\pm$ 2000 (A6 V20 BROOKFIELD at 20° C)
APPLICATION (5° C $\leq$ T $\leq$ 35° C)	Brush – Roller - Spray
DILUTION	20 - 30% with clear water
APPROXIMATE YIELD	7 - 8 sqm/Lt per coat
DRYING at 20° C	Out of dust: 10 - 15 minutes / Thoroughly dry: 24 hours
OVERCOATING INTERVAL	4 - 5 hours
V.O.C CONTENT	Less than 30 gr/l $\pm$ [Directive 2004/42/CE: (cat. A/a WB: 30)]
STORAGE AND SHELF LIFE	Store in a cool, dry, well ventilated area away from heat and direct sunlight. The product has a shelf life of 12 months when kept in original sealed packaging. It must be protected from frost.

CHARACTERISTICS AND FIELD OF APPLICATION

It is suitable as breathable, easy-to-apply finishing for interior masonry surfaces, finished with plaster or with similar materials.

The product can be dyed with universal pigments (pastel shades). The thinned product must be used within 2-3 days.

SUBSTRATE PREPARATION

NEW WALLS: the surface must be properly prepared, dry, clean, brushed, dusted off and free from any kind impurity. In case of need, apply one coat of water-based fixative as **HARZ-ACRIL** or **MURACRIL** or **NANOFIX**. Then, apply two coats of **MAXICOLOR**.

WALLS WITH EXISTING PAINTWORK: brush and clean the surface in order to remove flacking paints and anything that is not perfectly anchored to the substrate. In case of moulds ensure suitable treatment with **LINDOFIX**.

WARNINGS

Apply the product in the climatic conditions as mentioned above. Inappropriate conditions of application of the product are adversely affected in the drying time and the achievement of the optimum appearance and performance can be compromised. Drying may take longer when temperatures are lower and humidity is higher and some unsightly looking, translucent and sticky drops could appear. This temporary phenomenon does not affect the performance of the product and may be removed by washing the surface or waiting for the next rainfall event.

The product complies with C.L.P. European Regulation, in force from 1st June 2015.

All our products are of a high quality and subject to rigid quality control. The information given in this specification sheet is for guidance and is given in good faith but no liability can be assumed by Barozzi Vernici S.r.l. for the performance of the products and for final results, since skills of application and site conditions are beyond our direct control. The information contained in this document is strictly confidential and shall be the sole and exclusive property of Barozzi Vernici S.r.l.

