

## NUOVO SEGNALINEE – LINE MARKING PAINT

### ECO-FRIENDLY, LINE MARKING PAINT FOR SPORTS FIELDS.

<b>TYPE OF BINDER</b>	Modified acrylic
<b>ASPECT OF DRY FILM</b>	Matt
<b>AVAILABLE COLOURS</b>	White
<b>SPECIFIC WEIGHT</b>	1,70 Kg/lit +/- 0,05 at 20° C
<b>VISCOSITY</b>	17.000 cps +/- 1000 (A6 V20 BROOKFIELD at 20°C)
<b>APPLICATION (5°C ≤ T ≤ 35°C)</b>	Spray
<b>DILUTION</b>	Max 100% with clear water
<b>APPROXIMATE YIELD</b>	Unquantifiable
<b>DRYING at 20°C</b>	Out of dust: 5-10 minute / Touch dry: 30-60 minutes / Thoroughly dry: 2-4 hours
<b>OVERCOATING INTERVAL</b>	2-4 hours
<b>V.O.C CONTENT</b>	Less than 30 gr/lit [Directive 2004/42/CE: (cat. A/i WB: 140)]
<b>STORAGE AND SHELF LIFE</b>	Store in a cool, dry, well ventilated area away from heat and direct sunlight. The product has a shelf life of 12 months when kept in original sealed packaging. It must be protected from frost.

### CHARACTERISTICS AND FIELD OF APPLICATION

Eco-friendly, odourless, non-toxic, breathable paint suitable for line marking for sports fields. In case of skin contact it does not cause excoriations, skin irritations etc.

The thinned product must be used within 2-3 days.

### SUBSTRATE PREPARATION

Shake the product well and apply it by suitable line marking machine. Store and apply **NUOVO SEGNALINEE** at a temperature not lower than 5 °C. Wash tools with water immediately after use.

### WARNINGS

Apply the product in the climatic conditions as mentioned above. Inappropriate conditions of application of the product are adversely affected in the drying time and the achievement of the optimum appearance and performance can be compromised. Drying may take longer when temperatures are lower and humidity is higher and some unsightly looking, translucent and sticky drops could appear.

The product complies with C.L.P. European Regulation, in force from 1<sup>st</sup> June 2015.

*All our products are of a high quality and subject to rigid quality control. The information given in this specification sheet is for guidance and is given in good faith but no liability can be assumed by Barozzi Vernici S.r.l. for the performance of the products and for final results, since skills of application and site conditions are beyond our direct control. The information contained in this document is strictly confidential and shall be the sole and exclusive property of Barozzi Vernici S.r.l..*