

PRIMERSIL

WATER-BASED, ACRYLSILOXANE CONSOLIDATING FIXATIVE.

TYPE OF BINDER	Siloxane and acrylic binder in fine particles
ASPECT OF DRY FILM	Transparent
AVAILABLE COLOURS	Transparent
SPECIFIC WEIGHT	1,03 kg/lit +/- 0,02 at 20° C
VISCOSITY	10" ford viscosity cup F4 +/- 1" at 20° C
APPLICATION (5°C ≤ T ≤ 35°C)	Brush – Roller
DILUTION	100% with clear water (1:1)
APPROXIMATE YIELD	5 – 6 sqm/lit per coat
DRYING at 20°C	Out of dust: 15 – 20 minutes
OVERCOATING INTERVAL	5 – 6 hours
V.O.C CONTENT	Less than 30 gr/lit [Directive 2004/42/CE: (cat. A/h WB: 30)]
STORAGE AND SHELF LIFE	Store in a cool, dry, well ventilated area away from heat and direct sunlight. The product has a shelf life of 12 months when kept in original sealed packaging. It must be protected from frost.

CHARACTERISTICS AND FIELD OF APPLICATION

Suitable as siloxane primer based on special acrylsiloxane resins with fine particles. It is ideal for the preparation of wall surfaces, to be painted with siloxane systems. The high penetration capacity is linked to the type of surface and to the absorption degree.

The thinned product must be used within 2-3 days.

SUBSTRATE PREPARATION

Thin the product with up to 100% water for application, slowly add water (especially at the beginning), stirring at the same time. The wall must be dry, clean and brushed; eliminate all detaching parts, fill all imperfections.

In case of dirt and moulds wash with high-pressure washer and then apply **LINDOSTOP**.

WARNINGS

Apply the product in the climatic conditions as mentioned above. Inappropriate conditions of application of the product are adversely affected in the drying time and the achievement of the optimum appearance and performance can be compromised. Drying may take longer when temperatures are lower and humidity is higher and some unsightly looking, translucent and sticky drops could appear. This temporary phenomenon does not affect the performance of the product and may be removed by washing the surface or waiting for the next rainfall event.

The product complies with C.L.P. European Regulation, in force from 1st June 2015.

All our products are of a high quality and subject to rigid quality control. The information given in this specification sheet is for guidance and is given in good faith but no liability can be assumed by Barozzi Vernici S.r.l. for the performance of the products and for final results, since skills of application and site conditions are beyond our direct control. The information contained in this document is strictly confidential and shall be the sole and exclusive property of Barozzi Vernici S.r.l..