

SIVICOLOR

WATER-REPELLENT, BREATHABLE, WASHABLE, SELF-CLEANING, HIGHLY-COVERING PAINT FOR INTERIORS AND EXTERIORS.

TYPE OF BINDER	Modified acrylic in aqueous emulsion
ASPECT OF DRY FILM	Velvety matt
AVAILABLE COLOURS	White and UNISYSTEM tinting system
SPECIFIC WEIGHT	1,67 kg/lt +/- 0,05 at 20° C
VISCOSITY	18.000/ cps +/- 1.000 (A6 V20 BROOKFIELD at 20° C)
APPLICATION (5°C ≤ T ≤ 35°C)	Brush – Roller – Spray
DILUTION	20-30 % with clear water
APPROXIMATE YIELD	8 - 9 sqm/lt per coat
DRYING at 20°C	Touch dry: 20-30 minutes / Thoroughly dry: 24 hours
OVERCOATING INTERVAL	6 - 8 hours
V.O.C CONTENT	Less than 30 gr/lt [Directive 2004/42/CE: (cat. A/a WB: 30)]
STORAGE AND SHELF LIFE	Store in a cool, dry, well ventilated area away from heat and direct sunlight. The product has a shelf life of 12 months when kept in original sealed packaging. It must be protected from frost.

CHARACTERISTICS AND FIELD OF APPLICATION

It is suitable as finishing for interiors and exteriors, where, in addition to a velvet-like look, good breathability and self-cleaning properties are required. It is not suitable for north-facing walls or ETICS.

Diluted product must be used within 2-3 days.

SUBSTRATE PREPARATION

The surface (concrete, gypsum, mortar) must be properly prepared, dry, clean, brushed, dusted off and free from any kind of impurity. If necessary, apply one coat of water-based fixative as **NANOFIX** or **MURACRIL**, properly thinned, to consolidate the substrate.

FOR INTERIORS: in case of moulds ensure suitable treatment with **LINDOFIX**.

FOR EXTERIORS: in case of dirt and algae, wash with high pressure washing machine and then apply **LINDOSTOP**.

WARNINGS

Apply the product in the climatic conditions as mentioned above. Inappropriate conditions of application of the product are adversely affected in the drying time and the achievement of the optimum appearance and performance can be compromised. Drying may take longer when temperatures are lower and humidity is higher and some unsightly looking, translucent and sticky drops could appear. This temporary phenomenon does not affect the performance of the product and may be removed by washing the surface or waiting for the next rainfall event.

The product complies with C.L.P. European Regulation, in force from 1st June 2015.

All our products are of a high quality and subject to rigid quality control. The information given in this specification sheet is for guidance and is given in good faith but no liability can be assumed by Barozzi Vernici S.r.l. for the performance of the products and for final results, since skills of application and site conditions are beyond our direct control. The information contained in this document is strictly confidential and shall be the sole and exclusive property of Barozzi Vernici S.r.l..