Technical Data Sheet Code 233 Rif. 1910

STUCCOBEN

FRENCH STUCCO PASTE SUITABLE FOR WOOD AND MASONRY

TYPE OF BINDER	Vinyl in water emulsion
ASPECT OF DRY FILM	Matt, granulometry 10 µ
AVAILABLE COLOURS	White
SPECIFIC WEIGHT	1,750 kg/lt +/- 0,1 at 20° C
VISCOSITY	240.000 cps +/- 5.000 at 20° C
APPLICATION (5°C ≤ T ≤ 35°C)	Steel spatula
DILUTION	Ready to use – clear water
APPROXIMATE YIELD	Unquantifiable
DRYING at 20°C	Touch dry: 4 hours / Thoroughly dry: 24 hours
OVERCOATING INTERVAL	24 – 48 hours
STORAGE AND SHELF LIFE	Store in a cool, dry, well ventilated area away from heat and direct sunlight. The product has a shelf life of 12 months when kept in original sealed packaging. It must be protected from frost.

CHARACTERISTICS AND FIELD OF APPLICATION

It is the traditional stuccos suitable for wood and walls. Easy-to-apply, ideal to fill small irregularities on the surface. It can be easily sanded and may be coated with water-based paints or synthetic enamels.

SUBSTRATE PREPARATION

The surface must be completely dry and brushed. Any detaching part must be removed. In case of chalking surfaces, apply one coat of diluted fixative to consolidate the substrate.

WARNINGS

Apply the product in the climatic conditions as mentioned above. Inappropriate conditions of application of the product are adversely affected in the drying time and the achievement of the optimum appearance and performance can be compromised. Drying may take longer when temperatures are lower and humidity is higher and some unsightly looking, translucent and sticky drops could appear. This temporary phenomenon does not affect the performance of the product and may be removed by washing the surface or waiting for the next rainfall event.

The product complies with C.L.P. European Regulation, in force from 1st June 2015.

All our products are of a high quality and subject to rigid quality control. The information given in this specification sheet is for guidance and is given in good faith but no liability can be assumed by Barozzi Vernici S.r.l. for the performance of the products and for final results, since skills of application and site conditions are beyond our direct control. The information contained in this document is strictly confidential and shall be the sole and exclusive property of Barozzi Vernici S.r.l..