

TITAN

WASHABLE, WATER-BASED PAINT FOR INTERIORS, WITH HIGH COVERING PROPERTIES AND ANTI-MOULD ADDITIVES, EASY TO APPLY.

TYPE OF BINDER	Aqueous emulsion of modified acrylic
ASPECT OF DRY FILM	Velvet-like matt, smooth
WET-SCRUB RESISTANCE	CLASS 2 [UNI EN ISO 11998:2006]
AVAILABLE COLOURS	White, ice white and UNISYSTEM tinting system (pastel shades)
SPECIFIC WEIGHT	1,65 kg/lit +/- 0,05 at 20° C
VISCOSITY	13.000 cps +/- 2000 (A6 V20 BROOKFIELD at 20° C)
APPLICATION (5°C ≤ T ≤ 35°C)	Brush – Roller – Spray
DILUTION	15% - 25% with clear water
APPROXIMATE YIELD	8,5 - 9 sqm/lit per coat
DRYING at 20°C	Out of dust: 10 minutes / Touch dry: 40 - 60 minutes / Thoroughly dry: 3-4 hours
OVERCOATING INTERVAL	4 hours
V.O.C CONTENT	Less than 20 gr/lit [Directive 2004/42/CE: (cat. A/a WB: 30)]
STORAGE AND SHELF LIFE	Store in a cool, dry, well ventilated area away from heat and direct sunlight. The product has a shelf life of 12 months when kept in original sealed packaging. It must be protected from frost.

CHARACTERISTICS AND FIELD OF APPLICATION

TITAN is suitable as washable, breathable, water-based paint for interior wall surfaces, with high breathability and water repellency properties; controlled rheology. It allows to obtain finishes with high whiteness and very matt properties. It is very easy to use both by brush and roller and it maintains the right viscosity on walls, during application.

After its application, a pleasant fragrance is released. Thanks to its anti-mould power, it sanitizes walls, too.

The wet-scrub resistance is determined in accordance with the test method UNI EN ISO 11998:2006 "Determination of wet-scrub resistance and cleanability of coatings" through the measure of the loss of dry film thickness (ref. UNI EN 13300:2002) [The report 475/L date 11.10.2019 performed by GFC Chimica s.r.l. is available upon request].

SUBSTRATE PREPARATION

NEW WALLS (plaster, gypsum, plasterboard): the surface must be properly prepared, dry, clean, matured, dusted off and free from any kind of impurity or anything is not perfectly anchored to the substrate (sand included). Apply one coat of fixative as **MURACRIL** or **NANOFIX**, properly thinned, in order to consolidate the surface, avoid chalking and reduce paint consumption.

WALLS WITH EXISTING PAINTWORK (lime, tempera paint or breathable paint): brush and scrape the surface in order to remove flaking paints. In case of moulds ensure suitable treatment with **LINDOFIX**. Then, proceed as for new surface.

WARNINGS

Apply the product in the climatic conditions as mentioned above. Inappropriate conditions of application of the product are adversely affected in the drying time and the achievement of the optimum appearance and performance can be compromised. Drying may take longer when temperatures are lower and humidity is higher and some unsightly looking, translucent and sticky drops could appear.

The product complies with C.L.P. European Regulation, in force from 1st June 2015.

All our products are of a high quality and subject to rigid quality control. The information given in this specification sheet is for guidance and is given in good faith but no liability can be assumed by Barozzi Vernici S.r.l. for the performance of the products and for final results, since skills of application and site conditions are beyond our direct control. The information contained in this document is strictly confidential and shall be the sole and exclusive property of Barozzi Vernici S.r.l..